

GEUTEBRÜCK

5 MP Bullet Camera 2.7 - 12 mm G-Cam/EWPC-5240

G-Cam/EWPC-5240

5 MP outdoor Bullet Camera with IR LEDs and a focal length of 2.7 - 12 mm. The camera delivers up to 30 fps with H.264 at full resolution and can be operated via PoE or 12 VDC. The camera has an integrated wall bracket for easy ceiling or wall mounting or installation using a junction box.

Please refer to the data sheet for further technical information.

Technical specifications:

Image sensor (Chip): 1/2.7" Progressive CMOS

Picture format: 112:81 / 16:9 / 4:3

Video output (stream dependent): Composite video: 1 Vpp, 75 Ohm (BNC)

Scanning system: Progressive scan

Mega pixel: 5 MP (2720x x1976)

Pixel size: 2 µm

Minimum sensitivity: 0.08 Lux (Farbe) 0.008 Lux (S/W)

Day/Night function: Auto/Light on/Light Off/Day/Night/Light Sensor/Smart

IR-LEDs and sensor: IR-LEDs (850 nm; 8 ea)

IR-LED visible range: max. 40 m

Wide Dynamic Range: HDR (110 dB max.)

White balance: Auto/ATW/One Push/Manual

Exposure: Automatic / Manual

Shutter: 1~1/10K sec.

Back Light Compensation: On/Off (when TV system is w/o WDR only)

Digitale Noise Reduction: 2D/3D/Color NR

Text overlay: Yes

Interface: 10/100/1000 Mbps Ethernet

OSD-Menu: English/German/French/Italian/Korean/Simplified Chinese/Traditional

Chinese/Russian/Spanish/Japanese/Portuguese

Mirror-Function: On/Off

Portrait/Corridor View: 0°, 90°, 180°, 270°, Mirror

Compression: H.264/H264CCTV, H.265/H265CCTV, MJPEG

Picture rate (full resolution): H.264/H264CCTV or H.265/H265CCTV mit HDR: 5M@30fps + 720p@27fps

Picture rate: MJPEG: 1080p@30 fps

Video Streaming: Single, Dual, Triple + Quad Stream, configurable

Audio: 1x Line In, 1x Line Out/G.711, G.726, AAC, LPCM

Protocols: ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, HTTP, HTTPS, FTP, NTP, DDNS

ONVIF compatible: Yes; Profile S, G, Q, T

Access levels: Multiple user access levels with password protection

Network security: User Authentication, IP-Filter, HTTPS (TLS 1.0, 1.2), IEEE802.1X (SHA-1, SHA-2)

User Account: 20

Motion detection: Yes; 4 sets with 40x30 fields each, free settable

Alarm In/Output: 2x In (5 VDC/10 kOhm Pull Up Resistor; potential free), 1x Out (potential free)

Browser: Chrome, Firefox, Safari, Edge

Privacy masking: 5 adjustable masking zones (8 colors, rectangles, free scalable)

Data storage for set-up parameters: Internal non volatile storage and data transfer to PC

Picture Memory: µSD slot (128 GB max.)

Lens: f = 2.7 mm bis 12 mm (Motorized Vario)

Auto Focus: Yes (One-Touch-Function)

Digital zoom: x10

F-Stop: F1.6

Angle of view: Wide: 102,1° (H) x 70,3° (V) Tele: 31,5° (H) x 22,7° (V)

Operating temperature: - 55 °C to + 55 °C (w heater)

Humidity in operation: 10 - 90 % rel. humidity (non condensing)

Voltage supply: 12 VDC/24 VAC or PoE (IEEE 802.3af class 0 compatible)

Power consumption: Approx. 13.7 W @ 12 VDC/24 VAC

IP class / vandalism proof: IP 66 / IK10 (except front glass)

Connectors: RJ-45 for 10/100 Base/T Ethernet; 4p connector for Alarm I/O; Audio In/Out; 4p connector for external power supply; BNC connector for analogue video output, SD card slot

Dimensions in mm (Dia x H): 92 x 216.6

Weight: Approx. 780 g

Interface standard: ONVIF S, G, Q, T

Certifications: FCC, CE, RoHS

Licensing: G-Core

Accessories: Built-in heater

Optional accessories: G-Cam/EPMA-003 (5.04735)

Pole mount adapter

Turnkey delivery and installation or turnkey assembly and connection

Model: G-Cam/EWPC-5240

Brand: Geutebrück or similar