

5 MP Mini-Bullet Camera G-Cam/EWPC-5280

G-Cam/EWPC-5280

The Mini Bullet IP camera with a resolution of 5 MP features a particularly compact design in a weatherproof outdoor housing with sunshield. Despite the minimal design, a service-friendly motorized zoom lens with autofocus and IR illumination have been integrated for excellent image quality even at night. Please refer to the data sheet for further technical information.

Technical data:

Mega pixel: 5 MP (2720x x1936 eff.)

Image sensor: 1/2.7" Progressive CMOS

Picture format: 112:81 / 16:9 / 4:3

Lens: f = 2,7 mm to 12 mm Motorized Lens, P-Iris

F-Stop: F1.6

Digital zoom: optional digital zoom 10x

Angle of view: Wide: 102.1° (H) x 70.3° (V) Tele: 31.5° (H) x 22.7° (V)

Minimum sensitivity: 0,08 Lux (color), 0,008 Lux (BW)

IR-LED IR-LEDs: 850 nm / 15 m

Wide Dynamic Range: HDR Gen3 (130 dB max.)

White balance: One Push, Manual, AWB

Shutter: 1/425 s

Digitale Noise Reduction: 2D, 3D (low/middle/high/off), Color (low/middle/high/off)

Text overlay: Yes

Portrait/Corridor View: 0°, 90°, 180°, 270°

Compression: H.264/H264CCTV, H.265/H265CCTV, MJPEG

Resolutions: 5M, 4M, 1080p, 720p, 960 x 544, 360p

Video Streaming: Single, Dual, Triple + Quad Stream, configurable

Protocols: HTTP, TCP, FTP, RTSP, RTP, UDP, SMTP, SNMP, ICMP, IGMP, DHCP, UPnP, PPPoE, QoS, NTP, DDNS, ARP, IPv4/v6

Network security: User Authentication, IP-Filter, HTTPS (TLS 1.0, 1.2), IEEE802.1X (SHA-1, SHA-2)

ONVIF compatible: Yes; Profile S, G, Q, T

Motion detection: Yes; 4 sets with 40x30 fields each, free settable

Privacy masking: 5 adjustable masking zones (8 colors, rectangles, free scalable)

Edge recording: yes

Picture Memory: Slot for µSD, µSDHC (max. 128 GB)

Operating temperature: - 30 °C bis + 55 °

Humidity in operation: 10 - 90 % rel. humidity (non condensing)

Connectors: RJ-45 for 10/100/1000 Base/T Ethernet; connector for 12 VDC

Voltage supply: 12 VDC or PoE (IEEE 802.3af class 0 compatible)

Power consumption: Approx. PoE = 7.12W, DC12V = 6.34W

Dimensions in mm (Dia x L): Ø 86 x 162 mm

Cable length (from socket) x diameter: Approx. 30 cm x 6 mm

Weight: Approx. 385 g

Housing material and color: Aluminum/Plastic, near RAL 9003

IP class: IP 66

Certifications: EMC, FCC, CE, LVD

Licensing: G-Core

Optional accessories: G-Cam/EPMA003 Pole Mount Adapter (5.04735)

Application area: Outdoor

Turnkey delivery and installation or turnkey assembly and connection

Model: G-Cam/EWPC-5280

Brand: Geutebrück or equivalent