25.6 cm (10.1") Monitor

GD-ML-AP1031SD

Type: SD - LCD/TFT - Monitor
Item Code: GD-ML-AP1031SD
EAN CODE: 4260573060597

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.

Highlights

Continuous operation

This Grundig Security device is capable of operating 24/7 continuously on any day.

Features

- Metal cabinet
- High Contrast Ratio
- Displays a full, flat 10.1" (25.6cm) diagonal image
- Scratch protection glass with anti-reflection coating

GRUNDIG

Specifications GD-ML-AP1031SD

Display	
LCD Panel size:	25.6 cm (10.1") Diagonal AM-TFT LED Backlight
Pixels - Total:	1280 (H) x 800 (V)
Pixel Pitch:	0.192 mm (H) x 0.192 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	160° (H) ~ 160° (V)
Video	
Video Inputs:	1x Composite, BNC looped, 1x VGA, 1x HDMI
Video Standard:	PAL, NTSC
Brightness:	350 cd, m²
Contrast Ratio:	800:1
Number of Colours:	262K
Response Time:	12 ms
General	
Speakers:	yes
OSD (On Screen Display):	Yes, multi language
Accessories included:	Stand, power adapter, HDMI cable and remote control
I/O Interface	
Video Outputs:	1 Vpp, BNC
Audio Inputs:	1x 3.5mm jack (Line) , 1x HDMI
Approvals	
Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	>50,000 hours
Environmental	
Operating Temperature:	0 °C ~ +40 °C
Humidity:	Less than 90%, non condensing
Electrical	
Supply Voltage:	12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included
Power Consumption:	Max. 12 W
Mechanical	
Material:	Metal
Display protection:	Tempered acryl glass with anti-reflection coating
Vesa Mount:	75 x 75 mm
Dimensions:	185 x 250 x 38 mm (7,3 x 9,8 x 1,5 inch)
Weight:	1400 g (3.09 lb)